

4MP 52x Zoom Camera Module



Functions:

- 1/1.8" Progressive Scan 4MP CMOS
- 6.1-317mm;52x optical zoom
- Starlight technology
- Smart Features

Camera	
Image Sensor	1/1.8" Progressive Scan 4MP CMOS
Min. Illumination	Color:0.0005 Lux @(F1.4,AGC ON); Black:0.0001Lux @(F1.4,AGC ON);
Shutter Time	1/25 to 1/100,000s
Day & Night	IR Cut Filter
Lens	
Focal Length	6.1-317mm;52x optical zoom
Digital zoom	16x digital zoom
Aperture Range	F1.4-F4.7
Field of View	H: 61.8-1.6° (wide-tele);V: 36.1-0.9° (wide-tele)
Working Distance	100mm-2000mm (wide-tele)
Zoom Speed	Approx. 6 s (optical lens, wide-tele)
Compression	
Video Compression	H.265 / H.264 / MJPEG
Audio Compression	G.711a/G.711u/G.722.1/G.726/MP2L2/AAC/PCM
Image	
Resolution	50Hz: 25fps (2560*1440,1920 × 1080, 1280 × 960, 1280 × 720); 60Hz: 30fps (2560*1440,1920 × 1080, 1280 × 960, 1280 × 720)
Image Setting	Corridor mode, saturation, brightness, contrast and sharpness can be adjusted by client or browser
BLC	Support
Exposure Mode	Automatic exposure/aperture priority/shutter priority/manual exposure
Focus Control	Auto focus/one-time focus/manual focus//Semi-auto focus
Area Exposure/Focus	Support
Defog	Support
EIS	Support
Day & Night	Automatic, manual, timing, alarm trigger
3D Noise Reduction	Support

Modules Series | CB452

Image overlay	Support BMP 24 bit image overlay, optional region
ROI	Support three streams, set 4 fixed areas respectively
Network	
Network Storage	Supports Micro SD/SDHC/SDXC card (256G) for offline local storage Storage, NAS (NFS, SMB/CIFS are all supported)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,RTP,RTSP,RTCP,NTP,SMTP,SN MP,IPv6
Interface Protocol	ONVIF (PROFILE S, PROFILE G), GB28181-2016, domestic mainstream manufacturer agreement
General	
Consumption	2.5W MAX (ICR),4.5W MAX)
Weight	925g