

4MP 33x Starlight Network PTZ Camera



Functions:

- 1/2.8" Progressive Scan 4MP CMOS
- 5.5-180mm;33x optical zoom
- Starlight technology
- Smart Features
- IR distance up to 150m(800m optical)
- IP67

Camera	
Image Sensor	1/2.8" Progressive Scan 4MP CMOS
Min. Illumination	Color:0.001 Lux @(F1.5,AGC ON);Black:0.0005Lux @(F1.5,AGC ON);
Shutter Time	1/25 to 1/100,000s
Day & Night	IR Cut Filter
Lens	
Focal Length	5.5-180mm;33x optical zoom
Digital zoom	16x digital zoom
Aperture Range	F1.5-F4.0
Field of View	H: 57°(wide)-2.3° (tele);V: 32.6°(wide)-1.3° (tele)
Working Distance	100mm-1000mm (wide-tele)
Zoom Speed	Approx. 3.5s (optical lens, wide-tele)
Compression	
Video Compression	H.265 / H.264 / MJPEG
Audio Compression	G.711a/G.711u/G.722.1/G.726/MP2L2/AAC/PCM
Image	
Resolution	50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720); 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720)
Image Setting	Corridor mode, saturation, brightness, contrast and sharpness can be adjusted by client or browser
BLC	Support
Exposure Mode	Automatic exposure/aperture priority/shutter priority/manual exposure
Focus Control	Auto focus/one-time focus/manual focus
Area Exposure/Focus	Support
Defog	Support
EIS	Support
Day & Night	Auto(ICR) / Color / B/W

Portable Series | PTZ5A433-G

3D Noise Reduction	Support
Image overlay	Support BMP 24 bit image overlay, optional region
ROI	ROI supports one fixed region for each three-bit stream
Network	
Network Storage	Built-in memory card slot, support Micro SD/SDHC/SDXC, up to 128 GB; NAS (NFS, SMB/ CIFS)
Protocol	ONVIF(PROFILE S,PROFILE G) ,GB28181-2016
PTZ	
Pan Range	360° endless
Pan Speed	0.05°~80° /s
Tilt Range	-20°~90° or -30°~40°
Tilt Speed	0.05°~80°/s
Presets	255
Patrol Scan	6 patrols, up to 18 presets per patrol
Pattern Scan	4 , with the total recording time not less than 10 mins
Power Off Memory	Support
Infrared	
IR Distance	Up to 150m(800m optical)
IR Intensity	Automatically adjusted, depending on the zoom ratio
Port	
Audio I/O	NA
Alarm I/O	NA
General	
Power	DC 12~24V,40W(Max)
Working Temperature	-40°C~60°C
Humidity	Humidity 90% or less
Protection Level	Ip67, TVS 4000V Lightning protection, surge protection
Wiper	Optional
Mount Option	Vehicle mounting, Ceiling/tripod Mounting
Dimension	φ197×316
Weight	6.5kg

Portable Series | PTZ5A433-G

Accessories

Included:



AC24V/2.2A Power Adapter






970 Damping Bracket



Cable

Dimensions



Unit: