

4MP 52x Starlight Network PTZ Camera



Functions:

- 1/1.8" Progressive Scan 4MP CMOS
- 6.1-317mm;52x optical zoom
- Starlight technology
- Smart Features
- IR distance up to 800m
- IP66

Camera	
Image Sensor	1/1.8" Progressive Scan 4MP CMOS
Min. Illumination	Color:0.0005 Lux @(F1.4,AGC ON); Black:0.0001Lux @(F1.4,AGC ON);
Shutter Time	1/25 to 1/100,000s
Day & Night	IR Cut Filter
Lens	
Focal Length	6.1-317mm;52x optical zoom
Digital zoom	16x digital zoom
Aperture Range	F1.4-F4.7
Field of View	H: 61.8-1.6° (wide-tele);V: 36.1-0.9° (wide-tele)
Working Distance	100mm-2000mm (wide-tele)
Zoom Speed	Approx. 6 s (optical lens, wide-tele)
Compression	
Video Compression	H.265 / H.264 / MJPEG
Audio Compression	G.711a/G.711u/G.722.1/G.726/MP2L2/AAC/PCM
Image	
Resolution	50Hz: 25fps (2560*1440,1920 × 1080, 1280 × 960, 1280 × 720); 60Hz: 30fps (2560*1440,1920 × 1080, 1280 × 960, 1280 × 720)
Image Setting	Corridor mode, saturation, brightness, contrast and sharpness can be adjusted by client or browser
BLC	Support
Exposure Mode	Automatic exposure/aperture priority/shutter priority/manual exposure
Focus Control	Auto focus/one-time focus/manual focus//Semi-auto focus
Area Exposure/Focus	Support
Defog	Support
EIS	Support

Ultra Series | PTZ8A452-G

Day & Night	Automatic, manual, timing, alarm trigger
3D Noise Reduction	Support
Image overlay	Support BMP 24 bit image overlay, optional region
ROI	Support three streams, set 4 fixed areas respectively
Network	
Network Storage	Supports Micro SD/SDHC/SDXC card (256G) for offline local storage Storage, NAS (NFS, SMB/CIFS are all supported)
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, RTP, RTSP, RTCP, NTP, SMTP, SNMP, IPv6
Interface Protocol	ONVIF (PROFILE S, PROFILE G), GB28181-2016, domestic mainstream manufacturer agreement
Pan/Tilt	
Pan Range	360° (endless)
Pan Speed	0.05°/s ~ 90°/s
Tilt Range	-82° ~ +58° (auto reverse)
Tilt Speed	0.1° ~ 9°/s
Infrared	
IR Distance	Up to 800m
IR Intensity	Automatically adjusted, depending on the zoom ratio
Port	
Audio I/O	1 input, 1 output (optical)
Alarm I/O	1 input, 1 output (optical)
General	
Power	AC24V voltage input; Power consumption: ≤72w;
Working Temperature	-40°C ~ 60°C
Mounting	Mast mounting
Ingress Protection	Ip66
Dimension	4965 x 346
Weight	9.5 kg

Ultra Series | PTZ8A452-G

Accessories

Included:



AC24V/3A Power Adapter

Dimensions:

