

8-ch 2 HDD 4K Pro AI NVR



Max. 256 Mbps incoming; Max 8 Channel 8MP IPC input;
 16-channel 1080P decoding capability; Supports adaptive decoding
 Support 4K HDMI output; Up to 16 channels for playback;
 Support P2P, APP Alarm Push; Support AI search;
 AI by camera: Face Detection, Intrusion, Tripwire(classification of human/vehicles /non-motor), Object Detection, and SMD
 AI by NVR: Face Detection, Intrusion, Tripwire(classification of human/vehicles /non-motor), and SMD

Technical Specifications	
System	
OS	Embedded Linux
OS Operation Interface	Web/operating in local GUI
Perimeter Protection by Camera	
Performance	8 channels
Face Detection by Camera	
Performance	8 channels
Object Detection by Camera	
Performance	8 channels
SMD by Camera	
Performance	8 channels
Perimeter Protection by NVR	
Performance	4 channels
Face Detection by NVR	
Performance	4 channels
Face Recognition by NVR	
Performance	NA
SMD by NVR	
Performance	4 channels
Video&Audio Input	
Incoming bandwidth	256Mbps
Output bandwidth	256Mbps
IPC Input	8CH
Video&Audio Output	
VGA	1920×1080,1280×1024,1280×720
HDMI	3840×2160,1920×1080,1280×1024,1280×720
Audio Output	1CH,RCA(Line out,2Vp-p,300ohms)
Audio Encoding	

Pro AI Series | NVR6208E-I

Audio Compression	G.711A
Audio Bit Rate	64Kbps
Video&Audio Decoding	
IP channel Resolution	Up to 3840×2160
Video decoding	H.265 (Main Profile@L5.0 High-tie) /H.264 Up to High Profile@Level5.0)
Audio decoding	G.711A,G711U,G726
Synchronous Playback	8CH
Decoding Ability	16CH 1080P@30FPS/4CH 4K@30FPS
Preview	
Synchronous Preview	8
Multi-screen Display	1, 4, 8, 9, 16 views
Playback	
Record Mode	Manual; Schedule (general; MD; alarm; intelligent)
AI Search	Search by target classification (human, vehicle,non-motor vehicle)
Backup	USB device
Playback Function	1. Play; pause; stop; fast forward; fast backward; rewind; play by frame 2. Full screen; backup (cut/file) ; partially enlarge; audio on/off
Network	
Network Protocol	HTTP; TCP/IP; IPv4; UPnP; SNMP; RTSP;UDP; SMTP; NTP; DHCP; DNS; IP Filter; DDNS; FTP; P2P; Auto register
Mobile Phone Access	Android; iOS
Interoperability	ONVIF; SDK
Browser	IE8 or later
HDD	
SATA	2
ESATA	1
Max Capacity	14 TB
External Interface	
PoE Ports	0
Network Interface	2 RJ45 1000M
VGA	1
HDMI	2
CVBS	0
USB	2 USB 2.0 (on back panel), 1 USB 3.0 (On front)
RCA Input	1
RCA Output	1
Alarm Input	8
Alarm Output	4

Pro AI Series | NVR6208E-I

RS-232	1
RS-485	1
Other Function	
IPC Access	Support One-Click add IPC function
Two-way Talk	Yes
Alarm Linkage	Record; Snapshot; Buzzer; Log; Preset; Email
Picture Capture	Support JPEG Capture
General Parameter	
Front Panel	JS
Packing	405x365x123mm
Dimensions	1U 360x311.5x48mm
Weight	3Kg (No HDD)
Installation	Desktop Installation
Power Supply	DC 12V 3A
Working Temperature	-10°C--+55°C
Working Humidity	10%--90%
Consumption	20W(without HDD)
Certifications	
Certifications	CE/FCC

Dimensions

